

MASH036-W1-H
110V/60Hz

MASH048-W1-H
110V/60Hz

MASH060-W1-H
110V/60Hz

Technical specifications

Model	Wheel diameter	Dimension	Voltage			Max input power(W)	Air volume (cfm)			Air velocity (ft/sec)		Noise (dB)	Net weight (lb)	Air temperature (F)
	(in)		L x H x D (in)	(Hz)	(V-)		(A)	HI	LO	HI	LO			
MASH036-W1-H	5.5	35.4X10.3X13.2	60	110-120v	1.91	230	853	618	36	26	<55	61	59	
MASH048-W1-H	5.5	47.2X10.3X13.2	60	110-120v	2.50	300	1135	824	36	26	<57	77	59	
MASH060-W1-H	5.5	59X10.3X13.2	60	110-120v	2.75	330	1424	1030	36	26	<59	92	59	

Model	212 - 149 (F)					194 - 300 (F)					185 - 131 (F)				
	flow speed	Volume	Resistance	Temperature	Capacity	flow speed	Volume	Resistance	Temperature	Capacity	flow speed	Volume	Resistance	Temperature	Capacity
	(ft/sec)	(GPM)	(Pa)	(F)	(KW)	(ft/sec)	(GPM)	(Pa)	(F)	(KW)	(ft/sec)	(GPM)	(Pa)	(F)	(KW)
MASH036-W1-H	1.6	3.8	2036	127	20	1.27	3	1620	120	16	1.4	3.5	1870	116	13
MASH048-W1-H	1.6	7.7	2715	127	28	1.7	4	2160	120	21	1.9	4.7	2500	116	17
MASH060-W1-H	1.6	6.4	3390	127	36	2.13	5.1	2700	120	27	2.4	5.8	3115	116	21